

# TRUCK APPLICATION GUIDELINES

## PRIMAAX EX SERIES : Single/Tandem/Tridem Axle

	PAX 232	PAX 262	PAX 462	PAX 522	PAX 692	PAX 782
<b>Suspension Capacity</b>	10,500 kg	11,500 kg	20,000 kg	23,000 kg	25,000 kg	28,000 kg
<b>Axle Configuration</b>	Single	Single	Tandem	Tandem	Tridem	Tridem
<b>GCM Approval</b>	65,000 kg	80,000 kg	140,000 kg	160,000 kg	180,000 kg	180,000 kg
<b>Axle Travel</b>	150mm	150mm	150mm	150mm	150mm	150mm
<b>Ground Clearance</b>	270mm	270mm	270mm	270mm	270mm	270mm
<b>Ride Heights</b>	200-273mm	200-273mm	200-273mm	200-273mm	200-273mm	200-273mm
<b>Engine Torque Restrictions</b>	No Limit	No Limit	No Limit	No Limit	No Limit	No Limit
<b>Applications</b>	<ul style="list-style-type: none"> <li>▪ Rigid</li> <li>▪ Single Trailer</li> <li>▪ B-Double</li> <li>▪ Road Train Doubles &amp; Triples</li> <li>▪ High CoG &amp; live load applications</li> </ul>					

**Notes:** Suspension ratings in the above table to be used in conjunction with the respective axle manufacturer's recommendation/s

