

TRAILER APPLICATION GUIDELINES

HT230 SERIES

	HT230TA15-522A	HT230TA15-522L	HT230TA17-522
Ride Height	381 mm (15")	381 mm (15")	432 mm (17")
Liftable	No	Yes	Yes
Quik-Align	Standard	Standard	Standard
Underslung / Top Mount	Top Mount * ❖	Top Mount * ❖	Top Mount ❖
Tandem Group Ground Load	18,000 kg	18,000 kg	18,000 kg
Tri-Axle Group Ground Load	24,000 kg	24,000 kg	24,000 kg
Service : On/Off Highway	On / Off	On / Off	On / Off
Suspension Weight per Axle Set	138 kg	138 kg	145 kg
Applications	<ul style="list-style-type: none"> ▪ General 	<ul style="list-style-type: none"> ▪ General ▪ Liftable 	<ul style="list-style-type: none"> ▪ General



Options: * Below Chassis
❖ High Control Dolly



TRAILER APPLICATION GUIDELINES

HT250U SERIES

	HT250US.23	HT250US.25	HT250US.27
Ride Height	165 mm (6.5")	190 mm (7.5")	228 mm (9")
Liftable	No	No	Yes
Quik-Align	Standard	Standard	Standard
Underslung / Top Mount	Underslung *	Underslung *	Underslung *
Tandem Group Ground Load	18,000 kg	18,000 kg	18,000 kg
Tri-Axle Group Ground Load	24,000 kg	24,000 kg	24,000 kg
Service: On / Off Highway	On / Off	On / Off	On / Off
Suspension Weight per Axle Set	164 kg	171 kg	171 kg
Applications	<ul style="list-style-type: none"> ▪ Low ride requirements, e.g. car transport 	<ul style="list-style-type: none"> ▪ Low ride requirements ▪ B-Double lead trailer 	<ul style="list-style-type: none"> ▪ Low ride requirements ▪ B-Double lead trailer



Note: * Road friendly kit available



TRAILER APPLICATION GUIDELINES

LIFT KITS

	HTCL-001 *	HTCL-004 *	SLR ❖	S-24343	S-24657	97064-004
Lift Kit Installation Drawing #	D-20084	D-20242	N/A	97064-001	97064-002	49441-307
Suspension/s	HT250US	HT230 HT250 HT300	HT230TA- 522SLR	Intraax	Intraax	AANT / LDA
Suspension Installation Drawing #	98873-016	98873-036 HT250T-15-001 HT250T-17-001 HT300TB17-518	98873-012	98873-025	98873-027	98873-029
Ride Height	9"	15"; 17"	15"	15"; 17"; 19"	9"; 12"	15"
Kit Weight	39 kg	42 kg	18 kg	28 kg	25 kg	54 kg
Underslung / Top Mount	Underslung	Top mount	Top Mount	Top Mount	Underslung	Top Mount
Lift Position	Centre	Centre	Right Hand Side	Hanger	Hanger	Bolt On
Suits Beam Centre	35" <	35" <	N/A	N/A	N/A	N/A

Note: Not Lifiable: HT300-15, HT250U-6.5 and HT250U-7.5 models

* Only difference between HTCL-001 & HTCL-004 is the axle tower bracket

❖ Lift kit and suspension ordered together

